



#### Ünitex 7mm FR

The Ünitex was designed to offer high stiffness properties. The structural properties of the Ünitex allows to makes stand alone application.

## VALIDATED ECO-DECLARATION

## PRODUCT SPECIFICATIONS

#### Reference

Ünitex 7mm FR

#### Final manufacturing location

Saint-Elzear-de-Beauce, QC, GOS 2J0 CANADA

#### Composition

Black and white polyester fibers, Acrylic styrene, Recycled polyester fibers, Phosphate esters, Ammonium stearate, Copolymer of fluoroalkyl metacrylate.

#### **ATTRIBUTES**

#### **Recycled Content**

Pre-consumer: 6.7% Post-consumer: 6.7%

#### Sourcing of raw materials

The extraction locations of raw materials have been documented for 72.7% of the final product components, based on weight ratio.

FSC® Certification

Rapidly renewable materials

**Biobased materials** 

## **ENVIRONMENTAL IMPACTS**

Life Cycle Assessment

Product's carbon footprint

**Environmental Product Declaration** 

#### **INGREDIENTS AND EMISSIONS**

Declaration of chemical ingredients

Type of declaration

**Emission test** 

VOCs

Formaldehyde

Others

# Product's contribution to LEED® v4 ©Copyright 2016 Vertima inc. TECHNICAL PERFORMANCES

## Performance tests

ASTM C423 / SAA 0.23 / SAA with 25.4mm Air Gap 0.34 / NRC 0.23 / NRC with 25.4mm Air Gap 0.34 /ASTM E-84 (FLAME SPREAD) CLASS A

**Expected life** 

## MANUFACTURER'S ENVIRONMENTAL MANAGEMENT

ISO 14001 Certification

**Extended Producer Responsibility** (Take Back Program)

**Corporate Sustainability Report** 

(CSR: GRI,ISO 26000, BNQ 21000 ou autre)

## CERTIFICATIONS AND CONFORMITY REPORTS





Over the years, Texel has become a master in the needlepunch technology and the transformation and finishing of nonwoven materials according to various sophisticated processes, to the point today of developing and manufacturing innovative technical materials for numerous applications.

485, rue des Erables, Saint-Elzear-de-Beauce, QC GOS 2J0 CANADA www.feltkutur.com

MasterFormat®: **12 50 00** Validated Eco-Declaration:

VED17-1070-06

Original issue date: **2017/06** Period of validity: **2019/07** to **2020/07** 



## Ünitex 7mm FR





- Enhances stiffness without adding low-melt (bicomponent) fibers;
- · Wrinkle resistant when folded;
- Soft side (without resin) improves the look and feel;
- Hard side (with resin) gives structural and tackable properties.

#### **ATTRIBUTES**

#### **RECYCLED CONTENT**

Final product	Weight ratio	Pre-consumer	Post-consumer
Ünitex 7mm FR	100%	6.7%	6.7%
Components (with recycled content)	Weight ratio	Pre-consumer	Post-consumer
Recycled polyester fibers	13.3%	50%	50%

Validated Eco-Declaration - Recycled Content

Methodology: on-site audit, supply chain evaluation, analysis and validation of the recycled content data according to the weight ratio of each

of the components used in manufacturing the final product.

Vertima's procedure: VERT-032008-01, Second Edition.

#### **SOURCING OF RAW MATERIALS**

Weight ratio	Final manufacturing location
100%	Saint-Elzear-de-Beauce, QC GOS 2J0 CANADA

Validated Eco-Declaration – Sourcing of raw materials

Methodology: on-site audit, supply chain evaluation, analysis and validation of the sourcing of raw materials data according to the weight ratio of each of the components used in manufacturing the final product.

of the components used in manufacturing the final product Vertima's procedure: VERT-032008-02, Second Edition.

Weight ratio **Product Components** Transportation Black polyester fibers 33.3% **United States** Truck White polyester fibers 20.0% **United States** Truck Acrylic styrene 26.7% N/D Truck Recycled polyester fibers 13.3% South Carolina (US) Truck Phosphate esters 5.7% Truck United States Copolymer of fluoroalkyl metacrylate 0.7% **United States** Truck United States 0.3% Ammonium stearate Truck

The extraction locations of raw materials have been documented for 72.7% of the final product components, based on weight ratio.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.



Ünitex 7mm FR



## **ATTRIBUTES (CONTINUED)**

## **SOURCING OF RAW MATERIALS (CONTINUED)**



#### 1. EXTRACTION LOCATION RECYCLED POLYESTER FIBERS:

United States: Trenton, South Carolina

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.



Ünitex 7mm FR



### **TECHNICAL PERFORMANCES**

#### **PERFORMANCE TESTS**

Non-exhaustive list. Refer to the technical documentation of corrugated products for more details.

- Sound Absorption Coefficients by the Rebervation Room Method ASTM C423
- SAA 0.23
- SAA with 25.4mm air gap 0.34 SAA 0.23
- NRC 0.23
- NRC with 25.4mm air gap 0.34 NRC 0.23
- (Flame Spread) Class A ASTM E84

Validated Eco-Declaration – Performance tests Methodology: validation of documents attesting Performance tests Vertima's procedure: VERT-032011, Second Edition.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.



Ünitex 7mm FR



#### MANUFACTURER'S MANAGEMENT PROGRAM

#### **QUALITY MANAGEMENT SYSTEM (ISO 9001:2015)**

Certification number	Certification agency	Period of validity
0075281-00	Intertek	2004/01/13 to 2021/05/15

( ) 9001:20ds

Validated Eco-Declaration – ISO Certification Methodology: validation of documents attesting the ISO Certification. Vertima's procedure: VERT-032011, Second Edition.

#### **CERTIFICATION (BNQ 99002-01)**

Certification number	Certification agency	Period of validity
BNQ 9700/800	Bureau de normalisation du Québec	2010/05/07 to 2019/07/26



Validated Eco-Declaration – BNQ Certification Methodology: validation of documents attesting the BNQ Certification. Vertima's procedure: VERT-032011, Second Edition.

## MANUFACTURER'S ENVIRONMENTAL MANAGEMENT PROGRAM

Texel Technical Materials, Inc. undertakes to respect a policy which consists of using means that actively contribute to protecting the environment.

Our environmental policy traces the main axes of our actions for the coming years and defines our commitments in terms of environmental management:

- We operate our installations and execute our activities while aiming to minimize potential risks for the environment and the community;
- We promote the ongoing improvement of our environmental performance insofar as the biophysical reality and human health are concerned while respecting applicable laws and regulations;
- We continuously seek ways to reduce, reuse or recycle the waste we generate and, when necessary, eliminate it securely and responsibly;
- We collaborate with government authorities in the search for environmental solutions specific to our activities and in the development of standards which are technically justified and cost effective;
- We inform members of our Board of Directors and upper management of their environmental responsibilities in their respective field of activities;
- We developed an environmental management system to provide our executives, managers, and employees with the management tools needed to protect the environment.



Ünitex 7mm FR



## PRODUCT CONTRIBUTION SUMMARY

## LEED® v4 requirements for Building Design + Construction (BD+C)

New Construction, Core and Shell, School, Retail, Data Centers, Warehouse and Distribution Centers, Hospitality and Healthcare.

### LEED® v4 requirements for Interior Design + Construction (ID+C)

Commercial Interiors, Retail and Hospitality.

MATERIA	ALS AND RESOURCES	POINTS	PRODUCT CONTRIBUTIONS
	Building Product Disclosure and Optimization  – Sourcing of Raw Materials	1	ATTRIBUTES
MR	Option 2: Leadership extraction practices May also contribute to the location valuation factor if the product is sourced (extracted, manufactured, purchased) within 160 km of the project site.	point	Recycled Content Pre-consumer (6.7%) Post-consumer (6.7%)
INDOOR	ENVIRONMENTAL QUALITY	POINTS	PRODUCT CONTRIBUTIONS
Classrooms and C Option 2: Confirm the S12.60-2010 that roo requirements as spe	Minimum Acoustic Performance - Schools only Classrooms and Core Learning Spaces ≥ 20,000 Cubic Feet	Prerequisite	ATTRIBUTES
	Option 2: Confirm through calculations described in ANSI Standard S12.60-2010 that rooms are designed to meet reverberation time requirements as specified in that standard.  The acoustic test results for Ünitex 7mm FR will be supplied upon request.		<sup>1</sup> Ünitex 7mm FR may contribute to this prerequisite if the interior design is coherent with the prerequisite.
	Acoustic Performance  Meet the composite sound transmission class (STCc) ratings listed in		ATTRIBUTES
EQ	the Reference Guide. For all occupied spaces, meet the requirements, as applicable, for HVAC background noise, sound isolation, reverberation time, and sound reinforcement and masking.  The acoustic test results for Ünitex 7mm FR will be supplied upon request.	1-2 points <sup>1</sup>	Ünitex 7mm FR may contribute for the HVAC background noise and reverberation time requirements if the interior design is coherent with the credit.

#### LEED® v4 requirements for homes

Applies to single family homes, multi-family (one to three stories), or multi-family (four to six stories). Includes homes and multifamily low-rise and multifamily mid-rise.

MATE	RIALS AND RESOURCES	POINTS	PRODUCT CONTRIBUTIONS
	Environmentally Preferable Products  Option 1: Local Production  May also contribute to 0.5 point to the location valuation factor if the		ATTRIBUTES
MR	product is sourced (extracted, manufactured, purchased) within 160 km of the project site.	0.5	Recycled Content Pre-consumer (6.7%)
	Option 2: Environmentally Preferable Products	point	Post-consumer (6.7%)
	Ünitex 7.0mm FR does not contribute to 0.5 point. The final products should contain at least 25% post-consumer or 50% pre-consumer content.		Ünitex 7mm FR may contribute in another product assembly with additional recycled content.

It is important to consider that the total amount of possible points reflects the number of achievable points in each credit category. The product itself cannot achieve this score, as defined above, but is considered as a beneficial element in order to achieve LEED® credits.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.

Validated Eco-Declaration:
VED17-1070-06
Period of validity:
2019/07 to 2020/07