

The logo for 'feltkütür' is displayed on a black rectangular background. The word 'felt' is written in white lowercase letters, and 'kütür' is written in blue lowercase letters. The 'ü' in 'kütür' has a white dot above it.

feltkütür

**Build your own specifications with
the helper guide**

Adhesive felt 6.4mm (1/4")

Acoustic wall panel system

Panel texture: felted polyester

Composition: 100% polyester fibers, acrylic resin and acrylic adhesive

Panel thickness: 6.4mm (1/4")

Dimensions: 1.24m x 2.46m (+/-10%)

Colors available: grey Fermont, grey Westmont, grey Saint-Sébastien, tan Woburn, tan Percé, Wendake, blue Saint-Georges, green Saint-Marie, Rougemont.

Noise Reduction Coefficient (NRC): 0.23 **with no air gap**

Adhesion test ASTM D3330: Average of N/10mm at 75% RH on day 5 is 2.6 and Average of N/10mm at 45% RH on day 5 is 3.0.

Fire resistance ASTM E-84: FSI Class A and SDI Class A (felt only)

Fire resistance CAN/ULC-S102: FSR 20 and SDC 420 (felt only)

Recycled content: Up to 50% recycled polyester (post-consumer and/or post-industrial)

Reference product: Düotex Tahmea 6.4mm (1/4")