

The logo for 'feltkütür' is displayed on a black rectangular background. The word 'felt' is written in white lowercase letters, and 'kütür' is written in blue lowercase letters. The 'ü' in 'kütür' has a white dot above it.

feltkütür

**Build your own specifications with
the helper guide**

Honeycomb panel board

Acoustic wall panel system

Panel texture: felted polyester

Composition: 100% polyester fibers, acrylic resin and PU thermo adhesive

Panel thicknesses available: 1- $\frac{3}{4}$ "

Available sizes: 48" x 48" or 24" x 48" or 36" x 72"

Colors available: grey Fermont, grey Westmont, grey Saint-Sébastien, tan Woburn, tan Percé, Wendake, blue Saint-Georges, green Saint-Marie, Rougemont.

Noise Reduction Coefficient (NRC): 0.66

Fire resistance ASTM E-84: FSI Class A and SDI Class A (felt only)

Fire resistance CAN/ULC-S102: FSR 20 and SDC 420 (felt only)

Recycled content: Up to 50% recycled polyester (post-consumer and/or post-industrial)

Hardware: Pine spar

Installation: Screw the supplied wall strip onto your wall and hang the Tekboard Studio. Wall strip to be installed by the customer. Screws and drywall anchors not included. It is advisable to pre-drill the board to avoid splitting when screwing.

Product reference: Tekboard Studio



